

Chapter 4732 X-ray Definitions

PROPOSED REVISIONS TO 4732.0100

Preface

This is a DRAFT document. None of the changes are adopted or reflect current law.

MDH's proposed changes (or new language) is <u>underscored</u>. Existing language MDH proposes to remove or repeal is stricken with a <u>strike out</u>.

Of the 224 definitions in part 4732.0110, MDH is proposing to:

- Repeal 142
- Amend 73
- Add 10 new definitions

For each defined term, the action MDH is proposing (amend or repeal), and the rationale for the action, are included in the draft.

Guiding principles in this revision:

- Defining only those terms necessary and pertinent to MDH enforcement of ionizing radiation producing equipment
- Removing regulatory requirements from definitions
- Eliminating definitions that are obsolete or those that are not used in the rule chapter
- Referencing Minnesota Rules, Chapter 4731 for standard definitions (eg "dose", "rad") that span MDH's radiation control program, whenever possible, instead of having multiple definitions in different rule chapters

It is MDH's intent to continue work on its Radiation Therapy rulemaking (proposed Chapter 4733). With this in mind, most radiation therapy definitions are proposed for repeal from Minnesota Rules, Chapter 4732 and will be added as new definitions in the new Chapter 4733. These definitions will not be repealed if the Radiation Therapy rulemaking does not advance accordingly.

MDH encourages your review and welcomes your comments and feedback at xrayrules@state.mn.us.



4732.0100 DEFINITIONS.

Subpart 1. Scope. For purposes of this chapter, the terms in this part have the meanings given them.

Subp. 2. Absorbed dose. "Absorbed dose" has the meaning given in part 4731.0100, subpart 4 means the energy imparted by ionizing radiation per unit mass of irradiated material. The special unit of absorbed dose is the rad under the conventional system of measurement and is the gray under the SI system of measurement.

Subp. 3. Absorbed dose rate. "Absorbed dose rate" <u>has the meaning given in part</u> 4733.0105, <u>subpart ## means absorbed dose per unit time for machine with timers, or dosemonitor unit per unit time for linear accelerators.</u>

Subp. 4. Accelerator. "Accelerator" has the meaning given in part 4733.0105, subpart ## means any machine capable of accelerating electrons, protons, deuterons, or other charged particles in a vacuum and of discharging the resultant particulate or other radiation into a medium at energies usually in excess of 1 MeV. For purposes of this definition, linear accelerator, particle accelerator, and cyclotron are equivalent terms.

Subp. 5. Added filtration. "Added filtration" means filtration that is in addition to the inherent filtration.

Subp. 6. Adult. "Adult" means an individual 18 or more years of age or older.

Subp. 6a. Advanced practice registered nurse. "Advanced practice registered nurse" has the meaning given in Minnesota Statutes, section 148.171, subdivision 3.

Subp. 7. Air kerma (K). "Air kerma (K)" means the kinetic energy released in air by ionizing radiation. Kerma is determined as the quotient of dE by dM, where dE is the sum of the initial kinetic energies of all the charged ionizing particles liberated by uncharged ionizing particles in air of mass dM. The special name for the unit of kerma is the gray (Gy). The SI unit is joule per kilogram.

Subp. 8. Aluminum equivalent. "Aluminum equivalent" means the thickness of type 1100 aluminum alloy affording the same attenuation, under specified conditions, as the material in question.

Subp. 9. Annual. "Annual" means an <u>interval activity is done or is performed at intervals</u> not to exceed 12 months.

Subp. 10. Appropriate Allowable limit or appropriate limits. "Appropriate Allowable limit" or "appropriate limits" means the maximum permissible dose or doses of radiation that may be administered to the whole body or a given part of a human being.

Subp. 11. As low as reasonably achievable or ALARA. "As low as reasonably achievable" or "ALARA" means making every reasonable effort to maintain exposure to radiation as far

2 DRAFT 01/05/17

If there are accessibility concerns, we will provide an alternate format upon request to xrayrules@state.mn.us.

Commented [JC1]: Action: Amend by referencing definition in Minn. Rules chapter 4731 (Radioactive Materials).

Rationale: Whenever possible, refer to one rule chapter for standard definitions that span radiation control program. 4731.0100, subp. 4. Absorbed dose. "Absorbed dose" means the energy imparted by ionizing radiation per unit mass of irradiated material. The units of absorbed dose are the rad and the gray.

Commented [JC2]: Action: Amend by referencing proposed definition in proposed new rule chapter 4733 (Radiation Therapy).

Rationale: The term is more specific to a radiation therapy application.

Commented [JC3]: Action: Amend by referencing proposed definition in Radiation Therapy rule chapter (4733).

Rationale: The term is more specific to a radiation therapy application.

As proposed in new chapter 4733:

"Accelerator" means any machine capable of accelerating electrons, protons, deuterons, or other charged particles in a vacuum that discharges the resulting particulate or other radiation into a medium at energies usually in excess of one MeV.

Commented [JC4]: Action: Repeal.
Rationale: Term is not used in rule chapter.

Commented [JC5]: Action: Amend. Rationale: Improve syntax/readability.

Commented [JC6]: Action: Amend by adding new definition

Rationale: Align with APRN authority changes in Minn. Stat. ch. 148.

Commented [JC7]: Action: Repeal

Rationale: Common definition in industry; not needed in rule.

Commented [JC8]: Action: Repeal. **Rationale:** Term is not used in rule chapter.

Commented [JC9]: Action: Amend. Rationale: Improve syntax/clarity.

Commented [JC10]: Action: Amend by striking "appropriate" and inserting "allowable".

Rationale: Conform with usage in the rules. Term, as expressed, is not used in rule chapter, but "allowable limit"

Commented [JC11]: Action: Amend.

Commented [JC11]: Action: Amend. **Rationale:** Improve syntax/readability.



below the dose limits as is practical, consistent with the purpose for which the registered activity is undertaken, taking into account the state of technology, the economics of improvement in relation to benefits to the public health and safety, and other societal and socioeconomic considerations.

Subp. 12. Attenuation. "Attenuation" means the reduction of exposure rate upon passage of radiation through matter.

Subp. 13. Attenuation block. "Attenuation block" means a block or stack, having dimensions 20 centimeters or larger by 20 centimeters or larger by 3.8 centimeters, of type 1100 aluminum alloy or other materials having equivalent attenuation that is large enough to intercept the entire x-ray beam.

Subp. 14. Audit. "Audit" means a planned and documented activity performed according to procedures to determine, by examination and evaluation of objective evidence, the adequacy of and extent to which applicable elements of the quality assurance program have been developed, documented, and effectively implemented.

Subp. 15. Automatic exposure control or AEC. "Automatic exposure control" or "AEC" means a device that automatically controls one or more technique factors in order to obtain a required quantity of radiation at a preselected location or locations.

Subp. 16. Base plus fog density. "Base plus fog density" means the optical density of a film due to its base density plus any action of the developer on the unexposed silver halide crystals.

Subp. 17. Beam axis. "Beam axis" means a line from the source through the centers of the x-ray fields, or for therapy the axis of rotation of the beam-limiting device.

Subp. 18. Beam-limiting device or BLD. "Beam-limiting device" or "BLD" means a device used to restrict the dimensions of the x-ray field or useful beam.

Subp. 19. Beam-monitoring system. "Beam-monitoring system" has the meaning given in part 4733.0105, subpart ## means a system designed and installed to detect and measure the radiation present in the useful beam.

Subp. 20. Beam-scattering filter or foil. "Beam-scattering filter" or "foil" means a thin piece of material, usually metallic, placed in the beam to scatter a beam of electrons in order to provide a more uniform electron distribution in the useful beam.

Subp. 21. Bent beam linear accelerator. "Bent beam linear accelerator" means a linear accelerator geometry in which the accelerated electron beam must change direction by passing through a bending magnet.

Subp. 22. Bone densitometry system. "Bone densitometry system" means a medical device intended for medical purposes to measure bone density and mineral content by x-ray or gamma ray transmission measurements through the bone and adjacent tissues. This type of device may include signal analysis and display equipment, patient and equipment supports,

3 DRAFT 01/05/17

 $\textit{If there are accessibility concerns, we will provide an alternate format upon request to \underline{\textit{xrayrules@state.mn.us}}.$

Commented [JC12]: Action: Repeal.

Rationale: Common definition in industry; not needed in rule.

Commented [JC13]: Action: Repeal.

Rationale: The definition will be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

Commented [JC14]: Action: Repeal.

Rationale: Repeal definition of audit. Incorporate audit/review requirements in Quality Assurance Program rule part (.0520).

Commented [JC15]: Action: Repeal.

Rationale: Common industry term; not needed in rule.

Commented [JC16]: Action: Repeal.

Rationale: Term is not used in rule chapter.

Commented [JC17]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC18]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC19]: Action: Amend by referencing same definition in proposed new rule chapter 4733 (Radiation Therapy).

Rationale: The term is more specific to a radiation therapy application.

Commented [JC20]: Action: Repeal.

Rationale: The definition will be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

Commented [JC21]: Action: Repeal.

Rationale: The definition will be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

Commented [JC22]: Action: Amend.

Rationale: Clarify by using more precise language in SSRCR definition (Part F).



component parts, and accessories that uses electronically produced ionizing radiation to determine the density of bone structures of human patients.

Subp. 23. C-arm fluoroscope system. "C-arm fluoroscope system" means an a fluoroscopic x-ray system in which the image receptor and the x-ray tube housing assembly are connected or coordinated by a common mechanical support system to maintain a desired spatial relation relationship. Such a system allows a change in the direction of the beam axis with respect to the patient without moving the patient.

Subp. 24. Cabinet x-ray system. "Cabinet x-ray system" means an x-ray system with the x-ray tube installed in an enclosure independent of existing architectural structure except the floor on which it may be placed. The cabinet x-ray system is intended to:

A. contain at least that portion of a material being irradiated;

B. provide radiation attenuation; and

C. exclude personnel from its interior during generation of radiation.

Included are all x-ray systems designed primarily for the inspection of carry-on baggage at airline, railroad, and bus terminals and in similar facilities. An x-ray tube used within a shielded part of a building or x-ray equipment that may temporarily or occasionally incorporate portable shielding is not considered a cabinet x-ray system.

Subp. 25. Calibration. "Calibration" means: a determination of:

A. response or reading of an instrument relative to a series of known radiation values over the range of the instrument; or

B. the strength of a source of radiation relative to a standard.

A. the determination of the response or reading of an instrument relative to a series of known radiation values over the range of the instrument;

B. the determination of the radiation dose or exposure rate at a designated distance from a radiation source under specified conditions of measurement;

C. to check, adjust, or systematically standardize to graduations of a quantitative measuring instrument; and

D. to check, adjust, or systematically bring radiation-producing equipment into manufacturer's specifications.

Subp. 26. Cephalometric device. <u>"Cephalometric device" means a device intended for the radiographic visualization and measurement of the dimensions of the human head.</u>

Subp. 27. Certified cabinet x-ray system. "Certified cabinet x-ray system" means an x-ray system that has been certified according to Code of Federal Regulations, title 21, section 1010.2, as being manufactured and assembled pursuant to Code of Federal Regulations, title 21, section 1020.40.

4 DRAFT 01/05/17

If there are accessibility concerns, we will provide an alternate format upon request to xrayrules@state.mn.us.

Commented [JC23]: Action: Amend.

Rationale: Clarify by using more precise language in FDA definition. See SSRCR definition (Part F).

Commented [JC24]: Action: Amend.

Rationale: Striking requirement provisions from the definition. Propose to insert these provisions in affected rule parts.

(Cabinet x-ray system is used primarily for industrial applications but is also used in certain medical procedures involving tissue biopsy.)

Commented [JC25]: Action: Amend.

Rationale: Clarify by using more precise language in SSRCR definition, Part A.

Commented [JC26]: Action: Repeal. **Rationale:** Term is not used in rule chapter.

Commented [JC27]: Action: Repeal.

Rationale: Term is defined where it is mentioned in part

4732.1040.



Subp. 28. Certified components. "Certified components" means components of x-ray systems that are subject to the x-ray equipment performance standards adopted under Public Law 90-602, the Radiation Control for Health and Safety Act of 1968.

Subp. 29. Certified system. "Certified system" means an x-ray system that has one or more certified components.

Subp. 30. Changeable filters. "Changeable filters" means any filter, exclusive of inherent filtration, that can be removed from the useful beam through any electronic, mechanical, or physical process.

Subp. 31. Clinical range. "Clinical range" means the range of control console technique settings that a facility would use in its routine x-ray projections. Equipment performance tests are performed over clinical ranges.

Subp. 32. Coefficient of variation or C. "Coefficient of variation" or "C" means the standard deviation divided by the average of the parameters measured.

Subp. 33. Collimation. "Collimation" means the restriction of the useful beam to an appropriate area.

Subp. 34. Collimator. "Collimator" means a device used to limit the size, shape, and direction of the primary beam.

Subp. 35. Commissioner. "Commissioner" means the commissioner of the Department of Health or the commissioner's designee.

Subp. 36. Computed radiography <u>"Computed radiography" means a system of creating digital radiographic images that utilizes a storage phosphor plate instead of film in a cassette. Once the plate is exposed, a laser beam scans it to produce the digital data that is translated into an image.</u>

Subp. 37. Computed tomography or CT. "Computed tomography" or "CT" means the production of a tomogram by the acquisition and computer processing of x-ray transmission data.

Subp. 37a. Cone Beam Computed Tomography or (CBCT). Cone beam computed tomography or "CBCT" is a volumetric imaging modality. Volumetric data are acquired using two dimensional digital detector arrays, and a cone-shaped x-ray beam (instead of fan shaped) that rotates around the patient. Reconstruction algorithms may be used to generate images of any desired plane.

Subp. 38. Control panel. "Control panel" means the part of the x-ray control upon which where the switches, knobs, push buttons, keypads, touchscreens, and other hardware are mounted and necessary for manually setting the technique factors are mounted.

Subp. 39. CT conditions of operation. "CT conditions of operation" means all selectable parameters governing the operation of a CT system including, but not limited to, nominal tomographic section thickness, filtration, and the technique factors defined in subpart 195.

DRAFT 01/05/17

If there are accessibility concerns, we will provide an alternate format upon request to xrayrules@state.mn.us.

Commented [JC28]: Action: Repeal.

Rationale: Most human use components in use since 1974 are certified by FDA. MDH defines equipment performance standards in chapter 4732.

Commented [JC29]: Action: Repeal.

Rationale: Most human use components in use since 1974 are certified by FDA. MDH defines equipment performance standards in chapter 4732.

Commented [JC30]: Action: Repeal.
Rationale: Term is not used in rule chapter.

Commented [JC31]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC32]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC33]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC34]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC35]: Action: Amend.

Rationale: Preferred rule definition of commissioner includes commissioner's designee.

includes commissioner's designee.

Commented [JC36]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC37]: Action: Amend by adding new definition.

Rationale: CBCT is a newer imaging technology that is used in most dental facilities.

Commented [JC38]: Action: Amend.

Rationale: Clarify by including technological features found on most equipment. See SSRCR definition (Part F).

Commented [JC39]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.



Subp. 40. CT dose index or CTDI. "CT dose index" or "CTDI" means the integral from minus 7T to plus 7T of the dose profile along a line perpendicular to the tomographic plane divided by the product of the nominal tomographic section thickness (T) and the number of tomograms produced in a single scan (n), that is:

 $\frac{\text{CTDI} = 1/\text{nT} \cdot 7T + 7T \cdot D(z) \cdot dz}{2}$

where:

z = position along a line perpendicular to the tomographic plane;

D(z) = dose at position z;

T = nominal tomographic section thickness; and

n = number of tomograms produced in a single scan.

This definition assumes that the dose profile is centered around z=0 and that, for a multiple tomogram system, the increment of adjacent scans is nT.

Subp. 41. CT gantry. "CT gantry" means the tube housing assemblies, beam limiting devices, and detectors, as well as the supporting structures and frames that hold those components.

Subp. 42. CT number. "CT number" means the number used to represent the x ray attenuation associated with each elemental area of the CT image.

Subp. 43. CT scan. "CT scan" means the complete process of collecting x-ray transmission data for the production of a tomogram. This includes data collected simultaneously during a single scan for the production of one or more tomogram.

Subp. 44. CT scan increment. "CT scan increment" means the amount of relative displacement of the patient with respect to the CT system between successive scans measured along the direction of the displacement.

Subp. 45. CT scan time. "CT scan time" means the time between the beginning and end of x ray transmission data accumulation for a CT scan.

Subp. 46. Dead-man switch. "Dead-man switch" means a switch so constructed that a circuit closing contact can be maintained only by continuous pressure on the switch by the operator.

Subp. 47. Declared pregnant woman. "Declared pregnant woman" means a woman who has voluntarily informed the registrant, in writing, of her pregnancy and the estimated date of conception. The declaration remains in effect until the declared pregnant woman withdraws the declaration in writing, or is no longer pregnant.

Subp. 48. Densitometer. "Densitometer" means an instrument that measures the degree of blackening or radiographic density of a film due to radiation or light by measuring the ratio of the light intensity incident on the film to the light intensity transmitted by the film.

the dose profile along a line perpendicular to the tomographic plane divided by the product of the nominal tomographic section thickness (T) and the number of tomograms produced in a single scan (n)." (Supplied by comments from Geoffrey West, Ph.D., DABR, CHP, West

Rationale: MDH intends to incorporate proposed definition

"CT dose index means the integral minus 7T to plus 7T of

Commented [JC40]: Action: Repeal.

below in affected rule part.

Physics).

Commented [JC41]: Action: Repeal. **Rationale:** Term is not used in rule chapter.

Commented [JC42]: Action: Repeal.

Rationale: MDH will incorporate definition and SSRCR

definition (Part F) in affected rule part.

Commented [JC43]: Action: Repeal.

Rationale: Term is used once in the definition of "CT scan

time", which is proposed to be repealed.

Commented [JC44]: Action: Repeal. **Rationale:** Term is not used in rule chapter.

Commented [JC45]: Action: Repeal.

Rationale: Term is not used in rule chapter. "Scan time" is used 4 times in the definition of "Technique factors" (subp.

Commented [JC46]: Action: Repeal.

Rationale: Term as expressed in not used in 4732. MDH will incorporate definition provision into affected rule part.

Commented [JC47]: Action: Repeal.

Rationale: MDH will incorporate definition provisions in affected rule part (4732.0415).

Commented [JC48]: Action: Repeal.

Rationale: Term, as expressed, term is only used once in part 4732.0505. MDH proposes to incorporate definition provisions in affected rule part.

6 DRAFT 01/05/17

If there are accessibility concerns, we will provide an alternate format upon request to xrayrules@state.mn.us.



Subp. 49. Diagnostic radiological physicist. "Diagnostic radiological physicist" means an individual who is qualified to practice independently in the appropriate subfields for medical diagnostic physics and is:

A. certified in radiological physics or diagnostic radiological physics by the American Board of Radiology;

B. certified in diagnostic physics by the American Board of Medical Physics;

C. certified in diagnostic physics by the Canadian College of Medical Physics; or

D. a holder of a masters degree in medical physics, radiological sciences, or an equivalent field involving graduate study in physics applied to the application of radiation to humans from an accredited college or university and has at least two years of full-time practical training or supervised experience under an individual who meets the qualifications in item A, B, or C.

Subp. 50. Diagnostic x-ray X-ray imaging system. "Diagnostic x-ray X-ray imaging system" means an assemblage of components for the generation, emissions, and reception of x-rays and the transformation, storage, and visual display of the resultant x-ray image which that are designed and used for irradiation of any part of a body for the purpose of diagnosis or visualization.

Subp. 51. Digital radiography. "Digital radiography" means an x-ray imaging method (or radiography) which produces a digital rather than analog image. DR includes both computed radiography and direct digital radiography a radiographic image displayed on a video monitor after computer processing.

Subp. 52. Direct supervision. "Direct supervision" means a qualified practitioner must exercise general supervision and be present in the facility and immediately available to provide assistance and direction throughout the performance of the procedure. It does not mean that the licensed practitioner must be present in the room when the procedure is being performed guidance and instruction by a qualified individual who is physically present and watching the performance of the radiological operation or procedure and in such proximity that contact can be maintained and immediate assistance can be given as required.

Subp. 53. Dose. "Dose" has the meaning given in part 4731.0100, subpart 64 means absorbed radiation dose, radiation dose equivalent, effective radiation dose equivalent, committed radiation dose equivalent, committed effective radiation dose equivalent, or total effective radiation dose equivalent. For purposes of this chapter, "radiation dose" is an equivalent term.

Subp. 54. Dose equivalent or DE. "Dose equivalent" or "DE" has the meaning given in part 4731.0100, subpart 65 means a quantity used for radiation protection purposes that expresses on a common scale for all radiations the irradiation incurred by exposed persons. It is defined as the product of the absorbed radiation dose and the quality factor. For x-rays and gamma rays, the dose equivalent in rem is usually assumed to be numerically equal to either

7 DRAFT 01/05/17

If there are accessibility concerns, we will provide an alternate format upon request to xrayrules@state.mn.us.

Commented [JC49]: Action: Repeal.

Rationale: MDH will add and define "qualified medical physicist" and repeal all other related terms.

Commented [JC50]: Action: Amend.

Rationale: Strike "diagnostic" so that term is more generally applicable.

Commented [JC51]: Action: Amend.

Rationale: Updating and clarifying definition using SSRCR definition (Part F).

Commented [JC52]: Action: Amend.

Rationale: Update and clarify definition using SSRCR definition (Part F).

Commented [JC53]: Action: Amend by referencing definition in Minn. Rules chapter 4731 (Radioactive Materials).

Rationale: Whenever possible, refer to one rule chapter for standard definitions that span radiation control program. "Dose" or "radiation dose" means absorbed dose, dose equivalent, effective dose equivalent, committed dese equivalent, committed effective dose equivalent, or total effective dose equivalent.

Commented [JC54]: Action: Amend by referencing definition in Minn. Rules chapter 4731 (Radioactive Materials).

Rationale: Whenever possible, refer to one rule chapter for standard definitions that span radiation control program. "Dose equivalent" or "HT" means the product of the absorbed dose in tissue, quality factor, and all other necessary modifying factors at the location of interest. The units of dose equivalent are the rem and sievert.



the exposure in roentgens or the absorbed dose in rad. The special unit radiation dose equivalent is the rem under the conventional measurement system and is the Sievert under the SI measurement system.

Subp. 55. Dose limits or limits. "Dose limits" or "limits" has the meaning given in part 4731.0100, subpart 66 means the permissible upper bounds of radiation doses.

Subp. 56. Dose-monitoring system. "Dose-monitoring system" means a system of devices for the detection, measurement, and display of quantities of radiation that can be related to the absorbed dose at a given location within a defined geometry.

Subp. 57. Dose-monitor unit. "Dose-monitor unit" has the meaning given in part 4733.0105, subpart ## means a unit response from the dose-monitoring system from which the absorbed radiation dose has been calculated.

Subp. 58. Effective dose equivalent or HE. "Effective dose equivalent" or "HE" has the meaning given in part 4731.0100, subpart 69 means the sum of the products of the dose equivalent to each organ or tissue (HT) and the weighting factor (wT) applicable to each of the body organs or tissues that are irradiated.

Subp. 59. Electron-beam generator. <u>"Electron-beam generator" means a type of electron accelerator in which the electron beam is brought out into the atmosphere for irradiation purposes.</u>

Subp. 60. Electronic signature. "Electronic signature" has the meaning given in Minnesota Statutes, section 325L.02 (h) means an electronic sound, symbol, or process attached to or logically associated with a record, and executed or adopted by a person with the intent to sign the record according to Minnesota Statutes, chapter 325L.

Subp. 61. Exposure. "Exposure" <u>has the meaning given in part 4731.0100, subpart 77</u> means being exposed to ionizing radiation. The unit of exposure is the Roentgen in air (R). The SI unit is 2.58 x 10-4 coulombs per kilogram.

Subp. 62. Exposure rate. "Exposure rate" has the meaning given in part 4731.0100, subpart 79 means the exposure per unit of time, such as roentgen per minute, milliroentgen per hour. The SI unit is 10-4 coulombs per kilogram per hour.

Subp. 63. External beam radiation therapy. "External beam radiation therapy" means therapeutic irradiation in which the source of radiation is at a distance from the body.

Subp. 64. Facility. "Facility" means the location at which one or more sources of radiation are installed or located within one a building or one a vehicle, registered under at one physical address, or a complex, that is and are under one person's responsibility and oversight the same administrative control.

Subp. 65. Field emission equipment. "Field emission equipment" means equipment that uses an x-ray tube in which electron emission from the cathode is due solely to the action of an electric field.

8 DRAFT 01/05/17

If there are accessibility concerns, we will provide an alternate format upon request to xrayrules@state.mn.us.

Commented [JC55]: Action: Amend by referencing definition in Minn. Rules chapter 4731 (Radioactive Materials).

Rationale: Whenever possible, refer to one rule chapter for standard definitions that span radiation control program.

"Dose limits" or "limits" means the permissible upper

Commented [JC56]: Action: Repeal.

bounds of radiation doses.

Rationale: The definition will be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

Commented [JC57]: Action: Amend by referencing proposed definition in Radiation Therapy rule chapter (4733).

Rationale: The term is more specific to a radiation therapy application.

As proposed in new chapter 4733:

"Dose monitor unit" means a unit response from the dosemonitoring system used for calculating the absorbed radiation dose.

Commented [JC58]: Action: Amend by referencing definition in Minn. Rules chapter 4731 (Radioactive Materials).

Rationale: Whenever possible, refer to one rule chapter for standard definitions that span radiation control program.

"Effective dose equivalent" or "HE" means the sum of the products of the dose equivalent to the organ or tissue (HT) and the weighting factors (WT) applicable to each of the

Commented [JC59]: Action: Repeal. **Rationale:** Term is not used in rule chapter.

Commented [JC60]: Action: Amend.

Rationale: Clarify meaning by referencing the statutory definition.

Commented [JC61]: Action: Amend by referencing definition in Minn. Rules chapter 4731 (Radioactive Materials).

Commented [JC62]: Action: Amend by referencing definition in Minn. Rules chapter 4731 (Radioactive Materials).

Commented [JC63]: Action: Repeal.

Rationale: Definition proposed to be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

Commented [JC64]: Action: Amend.

Rationale: Include concept of "complex" and clarify what is meant by "administrative control".

Commented [JC65]: Action: Repeal.

Rationale: Term is used once in the definition of "technique factors. Propose incorporating definition provisions in affected rule part.



Subp. 66. Field-flattening filter. "Field-flattening filter" has the meaning given in part 4733.0105, subpart ## means a filter used to homogenize the absorbed dose rate over the radiation field.

Subp. 67. Filmless radiography or photostimulable storage phosphor (PSP) imaging.

"Filmless radiography" or "photostimulable storage phosphor (PSP) imaging" means a system that could employ employs reusable imaging plates, associated hardware and software to acquire and display digital projection radiographs. These imaging devices are known by a number of names including computed radiography (CR), photostimulable storage phosphor (PSP) imaging, or digital radiography (DR). In the digital form, PSP images are readily put into picture archiving and communications systems and viewed on a monitor rather than viewing an image on x ray film.

Subp. 68. Filter or filtration. "Filter" or "filtration" means material placed in the useful beam to preferentially absorb selected radiations.

Subp. 68a. Fluoroscopically-guided interventional procedure or FGI. "Fluoroscopically-guided interventional procedure" or "FGI" means an interventional diagnostic or therapeutic procedure performed via percutaneous or other access routes, usually with local anesthesia or intravenous sedation, which uses external ionizing radiation in the form of fluoroscopy to localize or characterize a lesion, diagnostic site, or treatment site, to monitor the procedure, and to control and document therapy.

Subp. 69. Fluoroscopic imaging assembly. "Fluoroscopic imaging assembly" means a subsystem in which x-ray photons produce a set of fluoroscopic or radiographic recorded images from the fluoroscopic image receptor. Fluoroscopic imaging assembly includes image receptors such as the image intensifier and spot-film device, electrical interlocks, if any, and structural material providing linkage between the image receptor and diagnostic source assembly.

Subp. 69a. Fluoroscopy. "Fluoroscopy" means a technique for generating x-ray images and presenting them simultaneously and continuously as visible images. This term has the same meaning as the term "radioscopy" in the standards of the International Electrotechnical Commission

Subp. 70. Focal spot. "Focal spot" means the area of the anode of the x-ray tube bombarded by the electrons accelerated from the cathode and from which the useful beam originates.

Subp. 71. Gantry. "Gantry" means the part of the system supporting and allowing possible movements of the radiation head.

Subp. 72. General purpose radiographic x-ray system. "General purpose radiographic x-ray system" means a radiographic x-ray system that, by design, is not limited to radiographic examination of specific anatomical regions.

Commented [JC66]: Action: Amend by referencing proposed definition in Radiation Therapy rule chapter (4733).

Rationale: The term is more specific to a radiation therapy application.

As proposed in new chapter 4733:

"Field-flattening filter" means a filter used to homogenize the absorbed dose over the radiation field including beamscattering filter or foil.

Commented [JC67]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC68]: Action: Amend by referencing proposed definition in Radiation Therapy rule chapter (4733).

Rationale: The term is more specific to a radiation therapy application.

As proposed in new chapter 4733:

"Filter" means material placed in the useful beam to change beam quality in radiation therapy systems.

Commented [JC69]: Action: Amend by adding new definition

Rationale: FGI is a newer technology that is used in most CVT procedures. See SSRCR, Part F.

Commented [JC70]: Action: Repeal.

Rationale: MDH will incorporate definition provisions in affected rule parts (4732.0875 and 4732.0306).

Commented [JC71]: Action: Amend by adding new definition.

Rationale: FGI is a newer technology that is used in most CVT procedures. From SSRCR, Part F.

Commented [JC72]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC73]: Action: Repeal.

Rationale: The definition proposed to be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

As proposed in chapter 4733:

"Gantry" means that part of the radiation therapy system supporting and allowing movements of the radiation head about a center of rotation.

Commented [JC74]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

9 DRAFT 01/05/17

If there are accessibility concerns, we will provide an alternate format upon request to xrayrules@state.mn.us.



Subp. 73. Gonad shield. "Gonad shield" means a protective barrier for the testes or ovaries.

Subp. 74. Gray or Gy. "Gray" or "Gy" has the meaning given in part 4731.0100, subpart 91 means the unit of absorbed radiation dose equal to one joule per kilogram. The conventional system equivalent is 100 rad.

Subp. 75. Half-value layer or HVL. "Half-value layer" or "HVL" means the thickness of a specified material that attenuates the beam of radiation to such an extent that the exposure rate is reduced to one half of its original value. The contribution of all scattered radiation, other than any that might be present initially in the beam concerned, is considered excluded.

Subp. 76. Healing arts. "Healing arts" means health professions for diagnostic or healing treatment of human and animal maladies illnesses that are regulated under Minnesota Statutes, chapter 147, 153, or 156; or section 148.01, 148.106, or 150A.05, subdivision 1, clause (4), for the lawful practice of medicine, dentistry, veterinary medicine, osteopathy, chiropractic, and podiatry.

Subp. 78. High radiation area. "High radiation area" has the meaning given in part 4731.0100, subpart 97 means any area, accessible to individuals, in which radiation levels from radiation sources external to the body could result in an individual receiving a radiation dose equivalent in excess of 0.1 rem (1.0 mSv) in one hour at 30 centimeters from any source of radiation or 30 centimeters from any surface that the radiation penetrates.

Subp. 78a. Image. "Image" means a radiograph or record produced on a device such as a fluorescent screen, processed film, x-ray image intensifier tube, solid-state detector, or gaseous detector or other successor technology that transforms incident x-ray photons into a visible image.

Subp. 79. Image intensifier. "Image intensifier" means a device, installed in its housing, that instantaneously converts an x-ray pattern into a corresponding light image of higher energy intensity.

Subp. 80. Image quality. "Image quality" means the overall clarity and detail of a radiographic image. Limiting spatial resolution (or resolving power), image sharpness, and image contrast are three common measures of image quality.

Subp. 81. Image receptor. "Image receptor" means a device such as a fluorescent screen or radiographic film, solid-state detector, or gaseous detector that transforms incident x-ray photons either into a visible image or into another form that can be made into a visible image by further transformations.

10 DRAFT 01/05/17

If there are accessibility concerns, we will provide an alternate format upon request to xrayrules@state.mn.us.

Commented [JC75]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC76]: Action: Amend by referencing definition in Minn. Rules chapter 4731 (Radioactive Materials).

Rationale: Whenever possible, refer to one rule chapter for standard definitions that span radiation control program. "Gray" or "Gy" is the SI unit of absorbed dose. One gray is equal to an absorbed dose of one joule/kilogram. One gray is also equal to 100 rads.

Commented [JC77]: Action: Repeal.

Rationale: MDH proposes to incorporate definition provisions in affected rule part

provisions in affected rule part

Commented [JC78]: Action: Amend. **Rationale:** Plain language edit.

Commented [JC79]: Action: Amend.

Rationale: Conforming to SSRCF Part F definition.

Commented [JC80]: Action: Amend by referencing definition in Minn. Rules chapter 4731 (Radioactive Materials).

Rationale: Whenever possible, refer to one rule chapter for standard definitions that span radiation control program. High radiation area means an area, accessible to individuals, in which radiation levels from radiation sources external to the body could result in an individual receiving a dose equivalent in excess of 0.1 rem (1 mSv) in one hour at 30 centimeters from the radiation source or 30 centimeters from any surface that the radiation penetrates.

Commented [JC81]: Action: Amend by adding new definition

Rationale: Updating and consolidating so there is only term to express "radiograph", "x-ray", etc...

Commented [JC82]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC83]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC84]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.



Subp. 82. Individual. "Individual" means a living human being.

Subp. 83. Individual monitoring. "Individual monitoring" means the assessment of dose equivalent by the use of individual monitoring devices or by the use of radiation survey data.

Subp. 84. Individual monitoring devices device. "Individual monitoring devices device" means devices a device designed to be worn by a single an individual for the assessment of dose equivalent. For purposes of this chapter, "personal monitoring dosimeter" and "dosimeter" are equivalent terms. Examples of an individual monitoring devices are device include a film badges, thermoluminescent devices, pocket ionization chambers, and optically stimulated luminescence devices.

Subp. 85. Industrial cabinet baggage system, "Industrial cabinet baggage system" has the meaning given for cabinet x-ray systems in subpart 24.

Subp. 86. Industrial vault radiography. "Industrial vault radiography" means industrial radiography conducted in an enclosure, shielded so that radiation levels at every location on the exterior meet the unrestricted limitations in this chapter.

Subp. 87. Industrial radiographer. "Industrial radiographer" means any individual who performs or who, in attendance at the site where ionizing radiation sources are being used, personally supervises industrial radiographic operations and who is responsible to the registrant for ensuring compliance with this chapter.

Subp. 88. Industrial radiographer's assistant. "Industrial radiographer's assistant" means an individual who uses radiographic exposure devices or radiation survey instruments in industrial radiography under the supervision of an industrial radiographer.

Subp. 89. Industrial radiography. "Industrial radiography" means an examination of the structure of materials by the nondestructive methods of utilizing ionizing radiation to make images. Industrial radiography does not include cabinet x-ray or the use of ionizing radiation-producing equipment to measure thickness, to identify levels and material in containers, or to analyze the chemical compositions. Industrial x-ray does not include the use of ionizing radiation-producing equipment in forensic, medical, or veterinary research.

Subp. 90. Inherent filtration. "Inherent filtration" means the filtration of the useful beam provided by the permanently installed components of the tube housing assembly.

Subp. 91. Inspection. "Inspection" means an official examination or observation of equipment, facilities, and procedures that includes, including but not limited to tests, radiation surveys, and monitoring and records review to determine compliance with rules, and requirements of the commissioner.

Subp. 92. Instrument traceability. "Instrument traceability" for ionizing radiation measurements means the ability to show that an instrument has been calibrated at specified time intervals using a national standard or a transfer standard. If a transfer standard is used, the calibration must be at a laboratory accredited by a program that requires continuing

11 DRAFT 01/05/17

If there are accessibility concerns, we will provide an alternate format upon request to xrayrules@state.mn.us.

Commented [JC85]: Action: Amend.

Rationale: Revise so that definition is consistent for irradiation purposes.

Commented [JC86]: Action: Amend.

Rationale: Writing in the singular is a best practice and the preferred form by the Revisor. Amended "personal monitoring dosimeter" because MDH proposes to repeal that definition in subp. 124.

Commented [JC87]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC88]: Action: Repeal.

Rationale: Term is not used in rule chapter.

Commented [JC89]: Action: Repeal.

Rationale: Term is used once in rule. Propose to replace

with "qualified operator".

Commented [JC90]: Action: Repeal.
Rationale: Term is not used in rule chapter.

Commented [JC91]: Action: Repeal.

Rationale: Used in two definitions "Added filtration" and "Changeable filters", both of which are proposed to be repealed.

Commented [JC92]: Action: Amend.

Rationale: Clarify that inspection is of "equipment, facilities, and procedures" and also includes "records review".

Commented [JC93]: Action: Amend.

Rationale: Striking requirement provisions that are in part

4732.0710.



participation in measurement quality assurance with the National Institute of Standards and Technology (NIST), or other equivalent national or international programs.

Subp. 93. Interlock. "Interlock" means a device that automatically causes a reduction of the exposure rate upon entry by personnel into a high radiation area. An interlocking device must prevent the start or continued operation of equipment unless certain predetermined conditions prevail.

Subp. 94. Ionizing radiation or radiation. "Ionizing radiation" or "radiation" means any radiation capable of producing displacing electrons from atoms or molecules, thereby producing ions. Examples: include alpha, beta, gamma, x-ray, and neutron radiation.

Subp. 95. Irradiation. "Irradiation" means the exposure of a living being or matter to ionizing radiation.

Subp. 96. Isocenter. "Isocenter" means a fixed point in space through which pass the central axes of radiation beams for all possible beam orientations and field sizes.

Subp. 97. Kilovolt peak or kVp. "Kilovolt peak" or "kVp" has the meaning given for peak tube potential in subpart 120.

Subp. 98. Lead equivalence or lead equivalent. "Lead equivalence" or "lead equivalent" means the thickness of lead affording the same attenuation, under specified conditions, as the material in question.

Subp. 99. Leakage radiation. "Leakage radiation" has the meaning given in part
4733.0105, subpart ## means radiation emanating from the radiation source assembly except
for the useful beam and radiation produced when the exposure switch or timer is not activated.

Subp. 100. Leakage technique factors. "Leakage technique factors" means the technique factors associated with the diagnostic or therapeutic source assembly that are used in measuring leakage radiation.

Subp. 101. Licensed practitioner of the healing arts. "Licensed practitioner of the healing arts" means health professionals for diagnostic or healing treatment of human and animal maladies illnesses, which are licensed under Minnesota Statutes, chapter 147, 153, or 156; or section 148.01, 148.106, or 150A.05, subdivision 1, clause (4), for the lawful practice of medicine, dentistry, veterinary medicine, osteopathy, chiropractic, and podiatry.

Subp. 102. Light field. "Light field" means the area <u>illuminated by light that simulates</u>
the radiation field of the intersection of the light beam from the beam-limiting device and one
of the set of planes parallel to and including the plane of the image receptor whose perimeter is
the locus of points at which the illumination is one-fourth of the maximum in the intersection.

Subp. 103. Line-voltage regulation. "Line-voltage regulation" means the difference between the no load and the load line potentials expressed as a percent of the load line potential. It is calculated using the following equation:

Percent line-voltage regulation = 100 (Vn - V1)/V1

12 DRAFT 01/05/17

If there are accessibility concerns, we will provide an alternate format upon request to xrayrules@state.mn.us.

Commented [JC94]: Action: Repeal.

Rationale: MDH proposes to incorporate definition

provisions in affected industrial rule part.

Commented [JC95]: Action: Amend.

Rationale: Form edits.

Commented [JC96]: Action: Repeal.

Rationale: The definition will be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

As proposed in new chapter 4733:

"Isocenter" means the center of the sphere through which the useful beam axis passes while the gantry moves through its full range of motions.

Commented [JC97]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC98]: Action: Amend by referencing proposed definition in Radiation Therapy rule chapter (4733).

Rationale: The term is more specific to a radiation therapy application.

As proposed in new chapter 4733:

"Leakage radiation" means radiation emanating from the diagnostic or therapeutic source assembly other than the useful beam."

Commented [JC99]: Action: Repeal.

Rationale: The definition will be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

Commented [JC100]: Action: Amend. Rationale: Plain language edit.

Rationale: Plain language edit.

Commented [JC101]: Action: Amend.

Rationale: Plain language edit.

Commented [JC102]: Action: Repeal. **Rationale:** Term is not used in rule chapter.



where:

Vn = no-load line potential; and

V1 = load line potential.

Subp. 104. mA. "mA" means milliampere.

Subp. 105. mAs. "mAs" means milliampere-second.

Subp. 106. Maximum line current. "Maximum line current" means the root-mean-square current in the supply line of an x-ray system operating at its maximum rating.

Subp. 107. Medical event. "Medical event" means a diagnostic administration of radiation for human use where a registrant is performing a fluoroscopically-guided interventional or CT procedure that exceeds the maximum dose limits and requires a report under part 4732.0610.

the administration of radiation received from radiation-producing equipment and includes:

A. therapeutic administration involving:

(1) the wrong patient;

(2) the wrong treatment modality;

(3) a dose to tissue other than the treatment site that is 50 percent or more of the dose expected from the administration defined in the written directive:

(4) a total radiation dose delivered that differs from the prescribed dose by 20 percent or more;

(5) a total radiation dosage delivered that differs from the prescribed dosage by 20 percent or more or falls outside the prescribed dosage range; or

(6) a fractionated radiation dose delivered that differs from the prescribed dose, for a single fraction, by 50 percent or more; and

B. when the patient radiation dose during a fluoroscopic procedure exceeds 600 rads for an adult.

Subp. 108. Medical particle accelerator. "Medical particle accelerator" has the meaning given for accelerator in subpart 4.

Subp. 109. Medical physicist. "Medical physicist" has the meaning given for diagnostic radiological physicist in subpart 49, or therapeutic radiological physicist in subpart 200.

Subp. 110. Medical uses use. "Medical uses use" means the intentional internal or external administration of radiation to human and animal patients or human research subjects.

13 DRAFT 01/05/17

If there are accessibility concerns, we will provide an alternate format upon request to xrayrules@state.mn.us.

Commented [JC103]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC104]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC105]: Action: Repeal.
Rationale: Term is not used in rule chapter.

Commented [JC106]: Action: Amend.

Rationale: Strike regulatory language and propose to add new medical event procedures in part 4732.0610.

Commented [JC107]: Action: Repeal. **Rationale:** Term is not used in rule chapter.

Commented [JC108]: Action: Repeal.

Rationale: MDH will add and define "qualified medical physicist" and repeal all other related terms.

Commented [JC109]: Action: Amend.

Rationale: Writing in the singular is a best practice and the preferred form by the Revisor.



Subp. 111. Megavolt (MV) or mega electron volt (MeV). "Megavolt," "MV," or "mega electron volt," "MeV," means the energy equal to that acquired by a particle with one electron charge in passing through a potential difference of 1,000,000 volts in a vacuum. Current convention is to use MV for photons and MeV for electrons.

Subp. 112. Moving beam radiation therapy. "Moving beam radiation therapy" means radiation therapy with continuous displacement of one or more mechanical axes relative to the patient during irradiation. It includes arc therapy, skip therapy, conformal therapy, and rotational therapy.

Subp. 113. Nominal tomographic section thickness. "Nominal tomographic section thickness" means the full width at half-maximum at the center of the cross-sectional volume over which x ray transmission data are collected.

Subp. 114. Nominal treatment distance. "Nominal treatment distance" means:

A. for electron irradiation, the distance from the scattering foil, virtual source, or exit window of the electron beam to the entrance surface of the irradiated object along the central axis of the useful beam:

B. for x-ray irradiation, the virtual source or target to isocenter distance along the entral axis of the useful beam; and

C. for nonisocentric equipment, the distance specified by the manufacturer.

Subp. 115. Nonstochastic effects. "Nonstochastic effects" means health effects the severity of which varies with the radiation dose, and for which a threshold is believed to exist. Radiation-induced cataract formation is an example of a nonstochastic effect.

Subp. 116. Occupational dose. "Occupational dose" means the dose received by an individual in the course of employment in which the individual's assigned duties for the registrant involve exposure to radiation producing equipment, whether or not the radiation-producing equipment is in the possession of the registrant. Occupational dose does not include doses received from background radiation, from any medical administration the individual has received, from exposure to individuals administered radioactive material and released in accordance with chapter 4731, from voluntary participation in medical research programs, or as a member of the public.

Subp. 117. Open-beam configuration. "Open-beam configuration" means an analytical x-ray system in which an individual could accidentally place some part of the body in the primary beam or secondary scattered beam path during normal operation.

Subp. 118. Optical density or O.D. "Optical density" or "O.D." means the logarithm of the incident light intensity minus the logarithm of the transmitted light intensity.

Subp. 119. Patient. "Patient" means an individual or animal subjected to healing arts examination, and diagnosis, or treatment.

Commented [JC110]: Action: Repeal.

Rationale: The definition will be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

Commented [JC111]: Action: Repeal.

Rationale: The definition will be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

Commented [JC112]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC113]: Action: Repeal.

Rationale: Definition proposed to be part of new chapter 4733 (Radiation Therapy). The term has no X-ray application and is more specific to a radiation therapy application.

Commented [JC114]: Action: Repeal.

Rationale: Definition proposed to be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

Commented [JC115]: Action: Repeal.

Rationale: MDH proposes to incorporate definition provisions in affected rule parts.

Commented [JC116]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC117]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC118]: Action: Amend.

Rationale: Modifying definition so that it applies to ionizing radiation use only.

14 DRAFT 01/05/17

If there are accessibility concerns, we will provide an alternate format upon request to xrayrules@state.mn.us.



Subp. 120. Peak tube potential. "Peak tube potential" means the maximum value of the potential difference across the x-ray tube during an exposure.

Subp. 121. Permanent radiographic installation. "Permanent radiographic installation" means a shielded enclosed room, cell, vault, or structure that is not moved and is not located at a temporary job site. The installation is designed or intended for radiography, and in which radiography is regularly performed.

Subp. 122. Person. "Person" means any individual, corporation, partnership, firm, association, trust, estate, public or private institution, group, agency, political subdivision of this state, and any legal successor, representative, agent or agency of the foregoing, excluding federal government agencies.

Subp. 123. Personal protective equipment or PPE garments. "Personal protective equipment" or "PPE garments" mean garments, including aprons, gloves, lead glasses, and thyroid collars made of radiation absorbing attenuating materials used to reduce radiation exposure.

Subp. 124. Personal monitoring dosimeter. "Personal monitoring dosimeter" has the meaning given for individual monitoring devices in subpart 84.

Subp. 125. Phantom. "Phantom" means a volume of material behaving in a manner similar to tissue with respect to the attenuation and scattering of radiation. This requires that both the atomic number (Z) and the density of the material be similar to that of tissue.

Subp. 126. Phototimer. "Phototimer" means a method for controlling radiation exposures to image receptors by measuring the amount of radiation that reaches a radiation monitoring device. A radiation monitoring device is part of an electronic circuit that controls the duration of time the x-ray tube is activated. "Phototimer" includes the meaning given for automatic exposure control in subpart 15.

Subp. 126a. Physician assistant. "Physician assistant" means a person registered according to an individual who is licensed under Minnesota Statutes, chapter 147A, who is qualified by academic training, practical training, or both to provide patient services as specified in the physician-physician assistant agreement under Minnesota Statutes, section 147A.20 recognized by the Minnesota Board of Medical Practice.

Subp. 127. Pixel or picture element. "Pixel" or "picture element" means an elemental area of a digital image.

Subp. 128. Port film or portal imaging. "Port film" or "portal imaging" means a radiographic film or electronic image taken with a therapeutic x-ray system to verify proper setup of the treatment field.

Subp. 129. Positive beam limiting or limitation or PBL. "Positive beam limiting or limitation" or "PBL" means the automatic or semiautomatic adjustment of an x-ray beam to the size of the selected image receptor, whereby exposures cannot be made without this adjustment.

DRAFT 01/05/17

If there are accessibility concerns, we will provide an alternate format upon request to xrayrules@state.mn.us.

Commented [JC119]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC120]: Action: Repeal.

Rationale: MDH proposes to incorporate definition

provisions in affected rule parts.

Commented [JC121]: Action: Amend. Rationale: Update definition from "garment" to "equipment" to reflect current usage. Change "absorbing" to "attenuating" because it is more technical and precise.

Commented [JC122]: Action: Repeal. Rationale: Term is defined in subpart 84.

Commented [JC123]: Action: Amend.

Rationale: Proposed language is consistent SSRCR part F

Commented [JC124]: Action: Repeal.

Rationale: Term is addressed by definition of "automatic exposure control" under subpart 84.

Commented [JC125]: Action: Amend.

Rationale: Update definition because PA's are now licensed, not registered. MDH proposes to cite the statute instead of naming Board of Medical Practice.

Commented [JC126]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC127]: Action: Repeal.

Rationale: Definition proposed to be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

Commented [JC128]: Action: Repeal.

Rationale: Propose to incorporate definition provisions in

affected rule parts.



Subp. 130. Position-indicating device or PID. "Position-indicating device" or "PID" means a device on dental x ray equipment used to indicate the beam position and to establish the source-to-skin distance.

Subp. 131. Prescribed dose. "Prescribed dose" means the total radiation dose and radiation dose per fraction as documented in the written directive or therapeutic order.

Subp. 132. Primary beam. "Primary beam" means radiation that passes through an aperture of the source housing by a direct path from the x-ray tube located in the radiation-producing equipment housing.

Subp. 133. Primary dose-monitoring system. "Primary dose monitoring system" means a system that will monitors the useful beam during irradiation and will terminates irradiation when a preselected number of dose monitor units have been acquired.

Subp. 134. Primary protective barrier. "Primary protective barrier" means the material, excluding filters, placed in the useful beam for protection purposes to reduce the radiation exposure.

Subp. 135. Protective apron. "Protective apron" see personal protective garments in subpart 123.

Subp. 136. Protective barrier or barrier. "Protective barrier" or "barrier" means a barrier of radiation-absorbing materials used to reduce radiation exposure and includes:

- $\underline{\text{1. "Primary protective barrier" means the material, excluding filters, placed in the useful} \\ \underline{\text{beam.}}$
- 2. "Secondary protective barrier" means a barrier sufficient to attenuate the stray radiation to the required degree.

Subp. 137. Protective glove. "Protective glove," see personal protective garments in subpart 123.

Subp. 138. Pulsed mode. "Pulsed mode" means operation of an x-ray system so that the x-ray tube current is pulsed by the x-ray control to produce one or more exposure intervals of less than one half second duration.

<u>Subp. 138a. Qualified medical physicist or QMP.</u> "Qualified medical physicist or QMP" means a service provider who meets each of the following credential for diagnostic medical physics under 4732.XXXX.

Subp. 138a. Qualified operator or operator. "Qualified operator" or "operator" means an individual who is authorized to operate diagnostic x-ray equipment for human use according to Minnesota Statutes, section 144.141, subdivision 5a.

Subp. 139. Quality assurance program. "Quality assurance program" means a registrant's site-specific resource manual that includes policies and procedures designed to reduce unnecessary radiation exposure by optimizing the performance of facility personnel and equipment an all-encompassing program including quality control that extends to

16 DRAFT 01/05/17

If there are accessibility concerns, we will provide an alternate format upon request to <u>xrayrules@state.mn.us</u>.

Commented [JC129]: Action: Repeal. **Rationale:** Term is not used in rule chapter.

Commented [JC130]: Action: Repeal.

Rationale: Definition proposed to be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

Commented [JC131]: Action: Repeal.

Rationale: Definition proposed to be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

Commented [JC132]: Action: Repeal.

Rationale: Definition proposed to be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

Commented [JC133]: Action: Repeal.

Rationale: Define primary and secondary barrier under the definition protective barrier.

Commented [JC134]: Action: Repeal.
Rationale: Contained within definition of PPE.

Commented [JC135]: Action: Amend.

Rationale: Clarify by defining primary and secondary

protective barrier. Based on lowa rules.

Commented [JC136]: Action: Repeal.

Rationale: Added to the definition of personal protective equipment.

Commented [JC137]: Action: Repeal. **Rationale:** Term is not used in rule chapter.

Commented [JC138]: Action: Amend by adding new definition.

Rationale: QMP is a nationally recognized industry term for individuals who perform medical physics on diagnostic x-ray equipment.

Commented [JC139]: Action: Amend by adding new definition.

Rationale: Placeholder. MDH proposes one term to define all operators of x-ray equipment.

Commented [JC140]: Action: Amend.

Rationale: Concept of radiation safety is missing in current definition. Proposed language is based NCRP Report No. 99 – Quality Assurance for Diagnostic Imaging. By National Council on Radiation Protection and Measurements, p 1-3. MDH proposes to incorporate highlighted language in the rule part governing quality assurance.



administrative, education, and preventive maintenance methods. It includes a continuing evaluation of the adequacy and effectiveness of the overall imaging program, with a view to initiating corrective measures when necessary. The nature and extent of this program will vary with the size and type of the facility, and the type of activities conducted.

Subp. 140. Quality control. "Quality control" means a series of standardized tests developed to detect changes in x-ray equipment function from its original level of performance distinct technical procedures that ensure the production of a satisfactory product. The objective of these tests, when performed routinely, allows prompt, corrective action to maintain x-ray image quality Its aim is to provide quality that is not only satisfactory but also dependable and economic. The quality control procedures are concerned directly with the equipment.

Subp. 141. Quarter or quarterly. "Quarter" or "quarterly" means at an intervals that not to exceed 12 consecutive weeks. is not less than 12 consecutive weeks and not more than 14 consecutive weeks.

Subp. 142. Rad. "Rad" <u>has the meaning given in part 4731.0100, subpart 186 means the special unit of absorbed dose. The SI equivalent is 0.01 gray.</u>

Subp. 143. Radiation. "Radiation" means ionizing radiation.

Subp. 144. Radiation area. "Radiation area" has the meaning given in part 4731.0100, subpart 188 means an area accessible to individuals in which the radiation levels could result in an individual receiving a dose equivalent in excess of 0.005 rem (0.05 mSv) in one hour at 30 centimeters from the source of radiation or from any surface that the radiation penetrates.

Subp. 145. Radiation detector or detector. "Radiation detector" or "detector" has the meaning given in part 4731.0100, subpart 189 means a device that in the presence of radiation provides a signal or other indication suitable for use in measuring one or more quantities of incident radiation.

Subp. 146. Radiation head. "Radiation head" means the structure from which the useful beam emerges has the meaning given in part 4733.0105, subpart ##.

Subp. 147. Radiation-producing equipment. "Radiation-producing equipment" means any device capable of producing radiation.

Subp. 148. Radiation protection. "Radiation protection" means the use of time, distance, shielding, and other personnel protective garments.

Subp. 148a. Radiation safety committee. "Radiation safety committee" means a representative group of qualified individuals in a CT or FGI facility responsible for the ongoing review and management of CT or FGI protocols, quality control, and quality assurance program to ensure that exams being performed achieve the desired diagnostic image quality at the lowest radiation dose possible while optimizing the capabilities of the equipment being used.

Subp. 149. Radiation safety officer. "Radiation safety officer" means an individual who is responsible for administering has the knowledge and training to apply appropriate radiation

17 DRAFT 01/05/17

If there are accessibility concerns, we will provide an alternate format upon request to xrayrules@state.mn.us.

Commented [JC141]: Action: Amend.

Rationale: Proposed language is based NCRP Report No. 99

– Quality Assurance for Diagnostic Imaging. By National
Council on Radiation Protection and Measurements

Commented [JC142]: Action: Amend.

Rationale: Adding "or quarterly" and making syntax edit.

Commented [JC143]: Action: Amend by referencing definition in Minn. Rules chapter 4731 (Radioactive Materials).

Rationale: Whenever possible, refer to one rule chapter for standard definitions that span radiation control program. Rad means the special unit of absorbed dose. One rad is equal to an absorbed dose of 100 ergs/gram or 0.01 joule/kilogram (0.01 Gy).

Commented [JC144]: Action: Repeal.

Rationale: Redundant. Amended definition of "ionizing radiation" definition to include "ionizing radiation <u>or</u> radiation".

Commented [JC145]: Action: Amend by referencing definition in Minn. Rules chapter 4731 (Radioactive Materials).

Rationale: Whenever possible, refer to one rule chapter for standard definitions that span radiation control program. Radiation area means an area accessible to individuals in which radiation levels could result in an individual receiving a dose equivalent in excess of 0.005 rem (0.05 mSv) in one hour at 30 centimeters from the radiation source or from any surface that the radiation penetrates.

Commented [JC146]: Action: Amend by referencing definition in Minn. Rules chapter 4731 (Radioactive

Rationale: Whenever possible, refer to one rule chapter for standard definitions that span radiation control program. "Radiation detector" or "detector" means a device that in the presence of radiation provides a signal or other indication suitable for use in measuring one or more quantities of incident radiation.

Commented [JC147]: Action: Repeal.

Rationale: Not the full meaning of radiation detector needed for CT.

Commented [JC148]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC149]: Action: Repeal.

 $\textbf{Rationale:} \ \ \text{Common industry definition; not needed in rule.}$

Commented [JC150]: Action: Amend by adding a new definition.

Commented [JC151]: Action: Amend.

Rationale: Syntax edits to clarify and improve readability.



protection standards <u>in a registered facility</u>, and has been assigned such responsibility by the registrant.

Subp. 150. Radiation therapy simulation system. "Radiation therapy simulation system" means a radiographic, fluoroscopic, or CT x-ray system including all software applicable to the process intended for localizing the volume to be exposed during radiation therapy and confirming the position and size of the therapeutic irradiation field.

Subp. 151. Radiograph. "Radiograph" means an image produced on a radiosensitive surface, such as a photographic film or digital plate, by radiation other than visible light, such as by x-rays passed through an object or by photographing a fluoroscopic image that results in a permanent record.

Subp. 152. Radiographic imaging system. "Radiographic imaging system" means any system where a permanent or semipermanent image is recorded on an image receptor by the action of ionizing radiation.

Subp. 152a. Radiology practitioner assistant or RPA—Radiology practitioner assistant" or "RPA" means an individual who is an advanced level radiographer registered with the American Registry of Radiologic Technologists and certified by the Certification Board for Radiology Practitioner Assistants. The individual is qualified by completion of an educational program recognized by the Board of Directors of the Certification Board for Radiology Practitioner Assistants. The RPA may provide patient services as specified in an agreement with a supervising radiologist.

Subp. 153. Rated line voltage. "Rated line voltage" means the range of potentials, in volts, of the supply line specified by the manufacturer at which the radiation-producing equipment is designed to operate.

Subp. 154. Rating. "Rating" means the operating limits as specified by the component manufacturer.

Subp. 155. Recording. "Recording" means producing a retrievable form of an image resulting from x-ray photons.

Subp. 156. Reference man. "Reference man" means a hypothetical aggregation of human physical and physiological characteristics. These characteristics may be used by researchers and public health workers to standardize results of experiments and to relate biological insult to a common base.

Subp. 157. Reference plane. "Reference plane" means a plane that is displaced from and parallel to the tomographic plane.

Subp. 159. Registered radiologist assistant or RRA. "Registered radiologist assistant" or "RRA" means a person who is an advanced level radiographer certified and registered in radiography by the American Registry of Radiologic Technologists and has successfully completed all elements of a radiologist assistant educational program recognized by the ARRT-

Commented [JC152]: Action: Repeal.

Rationale: Definition proposed to be part of new chapter 4733 (Radiation Therapy). Term is specific to radiation therapy application.

Commented [JC153]: Action: Repeal.
Rationale: Added to the definition of "image".

Commented [JC154]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC155]: Action: Repeal.

Rationale: MDH proposes to incorporate highlighted provision into affected rule part.

Commented [JC156]: Action: Repeal. **Rationale:** Term is not used in rule chapter.

Commented [JC157]: Action: Repeal. **Rationale:** Term is not used in rule chapter.

Commented [JC158]: Action: Repeal.
Rationale: Term is not used in rule chapter.

Commented [JC159]: Action: Repeal. **Rationale:** Term is not used in rule chapter.

Commented [JC160]: Action: Repeal.

Rationale: Term is not used in rule chapter.

Commented [JC161]: Action: Repeal.

Rationale: MDH proposes to incorporate highlighted provision into affected rule part.

18 DRAFT 01/05/17

If there are accessibility concerns, we will provide an alternate format upon request to xrayrules@state.mn.us.



The RRA would be able to provide patient services as specified in an agreement with a supervising radiologist.

Subp. 160. Registrant. "Registrant" means:

A. a person having administrative control of any radiation-producing equipment except those specifically exempted under this chapter and who is legally obligated to register with the commissioner according to this chapter; or

B. a person who is legally obligated to register with the commissioner as a service provider.

Subp. 161. Registration. "Registration" means registration with the commissioner according to this chapter.

Subp. 162. Rem. "Rem" has the meaning given in part 4731.0100, subpart 201 means a special unit of dose equivalence. The SI equivalent is 0.01 sievert.

Subp. 163. Restricted area. "Restricted area" " has the meaning given in part 4731.0100, subpart 201 means any area to which access or egress may be limited by the registrant for purposes of 5protection of individuals from exposure to-radiation.

Subp. 164. Retake or reject. "Retake" or "reject" means any diagnostic radiographic imaging that had to be retaken, reexposing the patient to radiation because of some error, failure, or degradation in the radiographic imaging process.

Subp. 165. Retake or reject analysis program. "Retake or reject analysis program" means an ongoing analysis of retakes or rejects that provides information about existing imaging problems in a radiology department.

Subp. 166. Roentgen or R. "Roentgen" or "R" has the meaning given in part 4731.0100, subpart 206 means a special unit of exposure. The roentgen is equal to 2.58 x 10-4 coulombs per kilogram of air.

Subp. 167. Scattered radiation or secondary radiation. "Scattered radiation" has the meaning given in part 4733.0105, subpart ## or "secondary radiation" means radiation that, during passage through matter, has been deviated in direction and may have also been modified by a decrease in energy.

Subp. 168. Secondary dose-monitoring system. "Secondary dose-monitoring system" means a system that will terminate irradiation if the primary dose monitoring system fails.

Subp. 169. Secondary protective barrier. "Secondary protective barrier" means a barrier sufficient to attenuate stray radiation.

Subp. 170. Sensitometer. "Sensitometer" means an instrument designed to reproducibly expose a piece of film to a number of different levels of light intensity. Commented [JC162]: Action: Amend by referencing definition in Minn. Rules chapter 4731 (Radioactive Materials).

Rationale: Whenever possible, refer to one rule chapter for standard definitions that span radiation control program. **Rem** means the special unit of any of the quantities expressed as dose equivalent. The dose equivalent in rems is equal to the absorbed dose in rads multiplied by the quality factor (1 rem = 0.01 sievert).

Commented [JC163]: Action: Amend by referencing definition in Minn. Rules chapter 4731 (Radioactive Materials).

Rationale: Whenever possible, refer to one rule chapter for standard definitions that span radiation control program. Restricted area means an area, access to which is limited by a licensee or registrant to protect individuals against undue risks from exposure to radiation and radioactive materials. Restricted area does not include areas used as residential quarters, but includes separate rooms in a residential building that are set apart as a restricted area.

Commented [JC164]: Action: Repeal.

Rationale: Term is addressed in part 4732.0535 (retake or reject analysis program).

Commented [JC165]: Action: Repeal.

Rationale: Definition is not needed. Part 4732.0535 describes and governs the retake or reject analysis program.

Commented [JC166]: Action: Amend by referencing definition in Minn. Rules chapter 4731 (Radioactive Materials).

Rationale: Whenever possible, refer to one rule chapter for standard definitions that span radiation control program. **Roentgen or R** means "Roentgen" a special unit of exposure equal to 2.58 x 10-4 coulomb per kilogram of air. One milliroentgens (mR) equals 0.001 roentgen.

Commented [JC167]: Action: Amend.

Rationale: The definition will be part of new chapter 4733 (Radiation Therapy). Term is specific to radiation therapy application.

As proposed in new new chapter 4733:

"Scattered radiation" means radiation that, during its passage through a substance, has been changed in direction and may also have been modified by a decrease in energy."

Commented [JC168]: Action: Repeal.

Rationale: The definition proposed to be part of new chapter 4733 (Radiation Therapy). Term is specific to radiation therapy application.

Commented [JC169]: Action: Repeal.

Rationale: Term is not used in rule chapter. Incorporate term in "Primary Protective Barrier", subp. 136.

Commented [JC170]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.



Subp. 171. Sensitometric strip. "Sensitometric strip" means a film exposed by a sensitometer, resulting in a gray scale range. The strips are used to measure the range of densities from minimum to maximum.

Subp. 172. Sensitometry. "Sensitometry" means a quantitative measurement of the response of film to exposure and development. Sensitometry is used to test the processor setup and stability.

Subp. 173. Service provider. "Service provider" means a person engaged in the business of assembling, installing, repairing, or replacing one or more components into <u>a</u> diagnostic or <u>an</u> industrial radiation-producing equipment system or subsystem, or conducting equipment performance evaluations on diagnostic or industrial equipment. Service providers must be registered with the commissioner under part 4732.0275.

Subp. 174. Shadow tray. "Shadow tray" means a device attached to the radiation head to support auxiliary beam-limiting material.

Subp. 175. Shutter. "Shutter" has the meaning given in part 4733.0105, subpart ## means a device attached to the tube housing assembly that can totally intercept the useful beam and has a lead equivalency not less than that of the tube housing assembly.

Subp. 176. SI equivalent. "SI equivalent" has the meaning given in part 4731.0100, subpart 214 means units that conform to the international system of units.

Subp. 177. Sievert or Sv. "Sievert" or "Sv" has the meaning given in part 4731.0100, subpart 215 means the SI unit of any quantities expressed as dose equivalent. The conventional system equivalent is the rem.

Subp. 178. Source. "Source" means the target or-focal spot of the x-ray tube or accelerator radiation-producing equipment.

Subp. 179. Source of radiation. "Source of radiation" means a device or equipment that emits or is capable of producing radiation. For purposes of this chapter, this is equivalent to radiation producing equipment.

Subp. 180. Source-to-image distance or SID. "Source to image distance" or "SID" means the distance from the source to the center of the input surface of the image receptor.

Subp. 181. Source-to-skin distance or SSD₊"Source-to-skin distance" or "SSD" means the distance between the source and the skin of the patient.

Subp. 182. Spot check. "Spot check" means a procedure that is performed to ensure that a previous calibration continues to be valid.

Subp. 183. Spot film. "Spot film" means a radiograph that is made during a fluoroscopic procedure to permanently record conditions that exist during that fluoroscopic procedure.

Subp. 184. Spot-film device. "Spot-film device" means a device intended to transport and position a radiographic image receptor between the x-ray source and fluoroscopic image

20 DRAFT 01/05/17

If there are accessibility concerns, we will provide an alternate format upon request to xrayrules@state.mn.us.

Commented [JC171]: Action: Repeal.
Rationale: Term is not used in rule chapter.

Commented [JC172]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC173]: Action: Amend.

Rationale: Striking requirement provision as it is already contained in rule part.

Commented [JC174]: Action: Repeal. **Rationale:** Term not used in rule chapter.

Commented [JC175]: Action: Amend.

Rationale: Definition proposed to be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

Commented [JC176]: Action: Amend by referencing definition in Minn. Rules chapter 4731 (Radioactive Materials).

Rationale: Whenever possible, refer to one rule chapter for standard definitions that span radiation control program.

SI equivalent means the international system of units.

Commented [JC177]: Action: Amend by referencing definition in Minn. Rules chapter 4731 (Radioactive Materials).

Rationale: Whenever possible, refer to one rule chapter for standard definitions that span radiation control program. Sievert or Sv means SI unit of any of the quantities expressed as dose equivalent. The dose equivalent in sieverts is equal to the absorbed dose in grays multiplied by the quality factor identified in subpart 183 (1 Sv = 100 rems).

Commented [JC178]: Action: Amend.

Rationale: Clarification.

Commented [JC179]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC180]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC181]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC182]: Action: Repeal.

Rationale: Essentially an EPE (equipment performance evaluation). Common industry definition; not needed in

Commented [JC183]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC184]: Action: Repeal.

Rationale: Obsolete.



receptor. Spot-film device includes a device intended to hold a cassette over the input end of the fluoroscopic image receptor to produce a radiograph.

Subp. 185. Stationary beam therapy. "Stationary beam therapy" means radiation therapy without relative displacement of the useful beam and the patient during irradiation.

Subp. 186. Step wedge. "Step wedge" means a quality control test tool made of type 1100 aluminum with 11 steps.

Subp. 187. Stepless adjustment. "Stepless adjustment" means a method of adjusting collimator blades continuously rather than in fixed increments.

Subp. 188. Stochastic effects. "Stochastic effects" means health effects that occur randomly and for which the probability of the effect occurring, rather than its severity, is assumed to be a linear function of dose without threshold. Hereditary effects and cancer incidence are examples of stochastic effects.

Subp. 189. Storage. "Storage" means a condition in which a device or radiation-producing equipment is not being used for an extended period of time and has been made inoperable.

Subp. 190. Storage area. "Storage area" means a location, facility, or vehicle that is locked or has a physical barrier to prevent accidental exposure to, tampering with, or unauthorized removal of the device, container, or source.

Subp. 191. Stray radiation. "Stray radiation" <u>has the meaning given in part 4733.0105, subpart ## means the sum of leakage radiation and scattered radiation</u>.

Subp. 192. Supervising physician. "Supervising physician" means a Minnesota licensed physician who accepts full medical responsibility for the performance, practice, and activities of a physician assistant according to Minnesota Statutes, section 147A.20, a registered radiologist assistant, or a radiology practitioner assistant.

Subp. 193. Survey or radiation survey. "Survey" or "radiation survey" means an evaluation of the radiological conditions and potential hazards incident to the use of radiation-producing equipment. When appropriate, such evaluation and includes, but is not limited to, tests, using physical examinations, and measurements of measuring levels of radiation.

Subp. 194. Target. "Target" <u>has the meaning given in part 4733.0105</u>, <u>subpart ## means</u> the part of an x-ray tube or accelerator onto which a beam of accelerated particles is directed to produce ionizing radiation or other particles.

Subp. 195. Technique factors. "Technique factors" means the conditions of operation for a specific procedure including source to image distance, kVp, mA, time, patient size, and image receptor type., specified as follows:

A. for capacitor energy storage equipment, peak tube potential in kV and quantity of charge in mAs;

21 DRAFT 01/05/17

If there are accessibility concerns, we will provide an alternate format upon request to xrayrules@state.mn.us.

Commented [JC185]: Action: Repeal.

Rationale: The definition proposed to be part of new chapter 4733 (Radiation Therapy). Term is specific to radiation therapy application.

Commented [JC186]: Action: Repeal.
Rationale: Term is already defined in rule part.

Commented [JC187]: Action: Repeal.

Rationale: Used once in definition of "variable-aperture beam-limiting device" which is proposed to be repealed.

Commented [JC188]: Action: Repeal.

Rationale: Term is not used in rule chapter.

Commented [JC189]: Action: Repeal.

Rationale: Concept of storage is confusing, and definition is technically incorrect for purposes of requiring registration and fee payment.

Commented [JC190]: Action: Repeal.

Rationale: Term is not used in rule chapter. MDH will add to proposed industrial provisions.

Commented [JC191]: Action: Amend.

Rationale: The definition will be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

As proposed in new chapter 4733:

"Stray radiation" means the sum of leakage and scattered radiation including x-ray, electron, and neutron.

Commented [JC192]: Action: Repeal.

Rationale: There is no requirement in rule currently that addresses written agreement for RRA or RPA.

Commented [JC193]: Action: Amend. Rationale: Clarifying to improve readability.

Commented [JC194]: Action: Amend.

Rationale: The term is more specific to a radiation therapy application.

As proposed in new chapter 4733:

"Target" means the part of a radiation-producing system used to intercept a beam of accelerated particles and cause emission of other radiation.

Commented [JC195]: Action: Amend.

Rationale: Condensing definition and will incorporate specific procedure requirements in affected rule parts.



B. for field emission equipment rated for pulsed operation, peak tube potential in kV, and number of x ray pulses;

C. for CT x-ray systems designed for pulsed operation, peak tube potential in kV, scan time in seconds, and either tube current in mA, x-ray pulse width in seconds, and the number of x ray pulses per scan, or the product of milliamperage, x-ray pulse width, and the number of x-ray pulses in mAs;

D. for CT x-ray systems not designed for pulsed operation, peak tube potential in kV, and either the tube current in mA and scan time in seconds, or the product of milliamperage and exposure time in mAs and the scan time when the scan time and exposure time are equivalent;

E. for phototimed or automatic exposure controlled equipment, all necessary indicators including anatomical, if applicable, that must be activated before exposure: and

F. for all other equipment, peak tube potential in kV and either tube current in mA and exposure time in seconds, or the product of milliamperage and exposure time in mAs-

Subp. 196. Television receiver. "Television receiver" means an electronic product designed to receive and display a television picture through broadcast, cable, or closed-circuit television.

Subp. 197. Temporary job site. "Temporary job site" means a location where radiography is performed, other than a location listed in a registration.

Subp. 198. Termination of irradiation. "Termination of irradiation" means the stopping of irradiation in a fashion that will not permit continuance of irradiation without the resetting of operating conditions at the control panel.

Subp. 199. Therapeutic radiation machine. "Therapeutic radiation machine" means x-ray or electron-producing equipment designed and used for external beam radiation therapy.

Subp. 200. Therapeutic radiological physicist. "Therapeutic radiological physicist" means an individual qualified to practice independently in the subfields for medical therapeutic physics who:

A. is certified in radiological physics or therapeutic radiological physics by the American Board of Radiology;

B. is certified in therapeutic radiological physics by the American Board of Medical Physics;

C. is certified in therapeutic radiological physics by the Canadian College of Medical Physics; or

D. holds a masters degree or doctor's degree in medical physics, radiological sciences, or an equivalent field involving graduate study in physics applied to the

22 DRAFT 01/05/17

 $\textit{If there are accessibility concerns, we will provide an alternate format upon request to \underline{\textit{xrayrules@state.mn.us}}.$

Commented [JC196]: Action: Repeal.

Rationale: Obsolete.

Commented [JC197]: Action: Repeal.

Rationale: MDH will incorporate provision in affected rule part 4732.1058 as follows:

Subpart 1. Applicability. This part applies to industrial radiation-producing equipment used for less than 30 days at a job site <u>location that is not listed on a registrant's registration or application</u>.

Commented [JC198]: Action: Repeal.

Rationale: Definition is proposed to be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

Commented [JC199]: Action: Repeal.

Rationale: Definition is proposed to be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

Commented [JC200]: Action: Repeal.

Rationale: Definition is proposed to be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.



application of radiation to humans from an accredited college or university and have at least one year of full time practical training and experience involving work in a radiation therapy facility under an individual who meets the qualifications in this item or item A. B. or C.

Subp. 201. Therapeutic-type protective tube housing. "Therapeutic type protective tube housing" means the definitions in items A to C.

A. For x-ray therapy equipment not capable of operating at 500 kilovolt peak (kVp) or above, the following definition applies: an x-ray tube housing so constructed that the leakage radiation at a distance of one meter from the source does not exceed one rad (0.01 Gy) in an hour when the tube is operated at its maximum rated continuous current for the maximum rated tube potential.

B. For x-ray therapy equipment capable of operation at 500 kilovolt peak (kVp) or above, the following definition applies: an x-ray tube housing so constructed that leakage radiation at a distance of one meter from the source does not exceed either one rad (0.01 Gy) in an hour or 0.1 percent of the useful beam dose rate at one meter from the source, whichever is greater, when the machine is operated at its maximum rated continuous current for the maximum rated accelerating potential.

C. In either case, small areas of reduced protection are acceptable provided the average reading over any 100 square centimeters area at one meter distance from the source does not exceed the values given in items A and B.

Subp. 202. Tomogram. "Tomogram" means an x-ray image of a thin section of the body.

Subp. 203. Tomographic plane. "Tomographic plane" means the geometric plane that is identified as corresponding to the output tomogram.

Subp. 204. Tomographic section. "Tomographic section" means the volume of an object whose x ray attenuation properties are imaged in a tomogram.

Subp. 205. Traceable to a standard. "Traceable to a standard" means a comparison, either directly or indirectly, to a standard maintained by the National Institute of Standards and Technology (NIST) and that all comparisons have been documented.

Subp. 206. Tube housing assembly. "Tube housing assembly" means the tube housing with tube installed. It includes high voltage and filament transformers and other appropriate elements when contained within the tube housing.

Subp. 207. Tube rating chart. "Tube rating chart" means the set of curves that specify the rated limits of operation of the tube in terms of the technique factors.

Subp. 208. Type 1100 aluminum alloy. "Type 1100 aluminum alloy" means an alloy of aluminum that has a nominal chemical composition of 99 percent minimum aluminum and 0.12 percent copper.

23 DRAFT 01/05/17

 $\textit{If there are accessibility concerns, we will provide an alternate format upon request to \underline{\textit{xrayrules@state.mn.us}}.$

Commented [JC201]: Action: Repeal.

Rationale: The definition is proposed to be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

Commented [JC202]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC203]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC204]: Action: Repeal.

Rationale: Common industry definition; not needed in rule.

Commented [JC205]: Action: Repeal.

Rationale: Definition is contained within definition of "instrument traceability".

Commented [JC206]: Action: Repeal.

Rationale: Common industry term; not needed in rule.

Commented [JC207]: Action: Repeal. **Rationale:** Obsolete term, not needed.

Commented [JC208]: Action: Repeal.

Rationale: Common industry term. MDH will incorporate in

rule



Subp. 209. Useful beam. "Useful beam" means the radiation emanating from the tube housing port or the radiation head and passing through the aperture of the beam limiting device when the exposure controls are in a mode to cause the system to produce radiation.

Subp. 210. Utilization log. "Utilization log" means a record of procedures conducted in a certain time frame and following a set of requirements:

A. medical in part 4732.0545;

B. fluoroscopic in part 4732.0825; and

C. industrial in part 4732.1040.

Subp. 211. Variable-aperture beam-limiting device. "Variable-aperture beam-limiting device" means a beam-limiting device that has a capacity for stepless adjustment of the x-ray field size at a given SID.

Subp. 195a. Verbal order. "Verbal order" means an order for an imaging procedure that is issued orally by an individual authorized under this chapter.

Subp. 212. Very high radiation area. "Very high radiation area" has the meaning given in part 4731.0100, subpart 259 means an area accessible to individuals, where radiation levels from radiation-producing equipment external to the body could result in an individual receiving an absorbed dose in excess of 500 rad (5 Gy) in one hour at one meter from any surface that the radiation penetrates.

Subp. 213. Virtual source. "Virtual source" means a point from which radiation appears to originate.

Subp. 214. Visible area. "Visible area" means the portion of the input surface of the image receptor over which incident x-ray photons are producing a visible image.

Subp. 215. Wedge filter. "Wedge filter" means an added filter effecting continuous change in transmission on all or part of the useful beam.

Subp. 216. Worker. "Worker" means an individual who engages in activities with sources of ionizing radiation that require registration by the commissioner and that are controlled by a registrant.

Subp. 217. Written directive or written order. "Written directive" or "written order" means a dated order either in writing or electronically for a specific patient, a specific imaging procedure, and has an indication of and identifies the licensed practitioner of the healing arts ordering the imaging procedure.

Subp. 218. X-ray control. "X-ray control" means a device, switch, or other similar means by which an operator a qualified operator initiates and terminates the radiation exposure. The x-ray exposure control may include associated equipment such as timers and back-up timers.

Commented [JC209]: Action: Repeal.

Rationale: The term is more specific to a radiation therapy application and proposed to be added new chapter 4733. As proposed in new chapter 4733:

"Useful beam" means the radiation that emanates from the activated tube-housing port or radiation head and passes through the aperture of the beam-limiting device.

Commented [JC210]: Action: Repeal.

Rationale: Definition provisions already contained in affected rule part.

Commented [JC211]: Action: Repeal. **Rationale:** Term is not used in rule chapter.

Commented [JC212]: Action: Amend by adding a new definition.

Rationale: Missing from rule chapter.

Additional requirement to be added in rule chapter: A person authorized to order must authenticate a verbal order within 48 hours of an imaging procedure.

Commented [JC213]: Action: Amend by referencing definition in Minn. Rules chapter 4731 (Radioactive Materials).

Rationale: Whenever possible, refer to one rule chapter for standard definitions that span radiation control program. Very high radiation area means an area accessible to individuals in which radiation levels from radiation sources external to the body could result in an individual receiving an absorbed dose in excess of 500 rads (5 Gy) in one hour at one meter from a radiation source or one meter from any surface that the radiation penetrates. At very high doses received at high dose rates, units of absorbed dose (rads and grays) are appropriate, rather than units of dose equivalent (rems and sieverts).

Commented [JC214]: Action: Repeal.

Rationale: Definition proposed to be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

Commented [JC215]: Action: Repeal.

Rationale: MDH to incorporate provision in the affected rule part governing veterinary medical radiographic systems.

Commented [JC216]: Action: Repeal.

Rationale: Definition proposed to be part of new chapter 4733 (Radiation Therapy). The term is more specific to a radiation therapy application.

Commented [JC217]: Action: Amend.

Rationale: Striking "written directive" since that pertains to radiation therapy.

Commented [JC218]: Action: Amend.

Rationale: Modifying "operator" because MDH is defining "gualified operator".



Subp. 219. X-ray equipment or X-ray machines. "X-ray equipment" or "X-ray machines" means an x-ray system, subsystem, or component. Types of x-ray equipment are listed in items A to D that includes:

A. "Mobile x-ray equipment" means x-ray equipment mounted <u>on a permanent</u> <u>base with wheels or casters for moving while completely assembled in a self-contained transport vehicle.</u>

B. "Portable industrial x-ray equipment" means industrial x-ray equipment designed to be brought to a temporary job site to perform temporary industrial radiography.

CB. "Portable x-ray equipment" means x-ray equipment <u>designed to be hand-carried</u> on wheels or casters and designed to be brought to a patient when the patient's condition does not permit transfer to a fixed location.

 $\Theta_{\mathcal{L}}$. "Stationary x-ray equipment" means x-ray equipment that is installed in a fixed location within a facility.

D. "Hand-held x-ray equipment" means x-ray equipment that is designed to be hand-held during operation.

Subp. 220. X-ray field. "X-ray field" means the area of the intersection of the useful beam and any one of the set of planes parallel to and including the plane of the image receptor, whose perimeter is the locus of points at which the exposure rate is one-fourth of the maximum in the intersection.

Subp. 221. X-ray generator. "X-ray generator" means a type of electron accelerator in which the electron beam is used mainly for the production of x-rays.

Subp. 222. X-ray high-voltage generator. "X-ray high-voltage generator" means a device that transforms electrical energy from the potential supplied by the x-ray control to the tube operating potential. The device may also include means for transforming alternating current to direct current filament transformers for the x-ray tube, high-voltage switches, electrical protective devices, and other appropriate elements.

Subp. 223. X-ray system. "X-ray system" means an assemblage of components for the controlled production of x-rays. It includes minimally an x-ray high-voltage generator, an x-ray control, a tube housing assembly, a beam-limiting device, <u>image receptor, x-ray table</u>, and the necessary supporting structures. Additional components that function with the system are considered integral parts of the system.

Subp. 223a. X-ray table. "X-ray table" means a patient support device with its patient support structure (tabletop) interposed between the patient and the image receptor during radiography and/or fluoroscopy. This includes, but is not limited to, any stretcher equipped with a radiolucent panel and any table equipped with a cassette tray (or bucky), cassette tunnel, fluoroscopic image receptor, or spot-film device beneath the tabletop.

Commented [JC219]: Action: Amend.

Rationale: Revising to be consistent with SSRCR, Part F, definition of "x-ray equipment". Adding "or x-ray machines" to be consistent with Minn. Stat. 144.121.

Commented [JC220]: Action: Repeal.

Rationale: Common industry term; not needed in rule.

Commented [JC221]: Action: Repeal.

Rationale: Term in not used in rule chapter.

Commented [JC222]: Action: Repeal.

Rationale: Common industry term; not needed in rule.

Commented [JC223]: Action: Amend.

Rationale: Specifying "image receptor" and "x-ray table" as additional components.

Commented [JC224]: Action: Amend by adding a new definition.

Rationale: Missing from rule chapter, based on SSRCR Part F. Also added to definition of "x-ray system".



Subp. 224. X-ray tube or tube. "X-ray tube" or "tube" means an electron tube designed to be used primarily for the production of x rays.

Subp. 225. Year. "Year" means a period of time consisting of 12 consecutive months.

Commented [JC225]: Action: Repeal.

Rationale: Common industry term; not needed in rule.

Commented [JC226]: Action: Repeal.

Rationale: Not all instances of "year" in rule chapter align with this definition. May need to specify in each rule part where we mean 12 consecutive months.